

DuraStack® Pro for Grease Duct Applications Now Available

DuraVent has obtained UL approvals for DuraStack® Pro for use in Grease Duct applications.

DuraStack Pro Models DAS1, DIS1, DIS2, and DIS4 are now tested and listed to UL 1978, Standard for Grease Duct. See information below and visit www.DuraVent.com for more details.

Model DAS1 (Double wall, 1" air insulation)	
UL 103 - Building Heating Appliance Chimney	5" - 36" ID
UL 2561 - 1400° Fahrenheit Chimney	5" - 36" ID
UL 1978 - Grease Duct ULC S662 - Grease Duct	5" - 36" ID

Model DIS1, DIS2, DIS4 (Double wall, fiber insulation)	
UL 103 - Building Heating Appliance Chimney	5" - 36" ID
UL 103 HT - Building Heating Appliance Chimney(Type HT)	5" - 24" ID
UL 2561 - 1400° Fahrenheit Chimney	5" - 36" ID
UL 1978 - Grease Duct ULC S662 - Grease Duct	5" - 36" ID

Clearance to Combustible (Unenclosed Surrounding) (from the outer band) Grease Duct - UL 1978 (500°F)

Ø	DAS1	DIS1	DIS2 and DIS4
5	4	2	1
6	5	2	1
7	5	2	1
8	5	2	1
9	5	2	1
10	5	2	1
11	5	2	1
12	6	2	1
13	6	2	1
14	6	2	1
16	6	3	1
18	7	3	2
20	7	3	2
22	7	3	2
24	8	3	2
26	8	4	2
28	8	4	2
30	9	4	2
32	9	4	3
34	9	4	3
36	10	5	3

Dimensions are in inches

Note: Clearance to non combustible is 0" for all models and diameter



For current pricing and availability, please call customer service at (800) 835-4429.

Information published in all DuraVent bulletins is current at time of publication and is subject to change without notice.